

- Full HD filter
- Turbo koeling/verwarming
- Sleep mode
- Energie spaarstand



Free Joint Multi Wand Maldives warmtepomp

Wand Maldives		AR07JSFPEWQNEU	AR09JSFPEWQNET	AR12JSFPEWQNET	AR18FSFPDGMNEU	AR24FSFPDGMNEU
Infrarood afstandsbediening		√	√	√	√	√
Bediening via WiFi		-	-	-	-	-
Koelen	W	2.000	2.500	3.500	5.000	6.800
Verwarmen	W	2.200	3.200	4.000	6.000	7.800
Luchtvolume	m3/uur	474	630	690	852	1.068
Ontvochtiging	l/uur	0,9	0,9	1,2	2,5	2,5
Spanning	V/Fase/Hz	230/1/50	230/1/50	230/1/50	230/1/50	230/1/50
Opgen. vermogen	W	30	30	30	40	60
Nom. stroom koelen/verwarmen	A	0,18/0,18	0,30/0,30	0,30/0,30	0,30/0,30	0,45/0,45
Aders voeding	BI/BU	3/BU	3/BU	3/BU	3/BU	3/BU
Aantal aders	BI/BU	3+2	3+2	3+2	3+2	3+2
Communicatie	AC/RS485	RS485	RS485	RS485	RS485	RS485
Geluidsdruk niveau laag/hoog	dB(A)	23/31	23/37	23/38	27/40	29/44
Geluidsvermogen	dB(A)	53	56	57	57	62
Volledig HD filter		√	√	√	√	√
MPI		-	-	-	-	-
Auto herstart		√	√	√	√	√
Energie spaarstand		√	√	√	√	√
Geavanceerde slaap mode		√	√	√	√	√
Breedte	mm	820	820	820	1.065	1.065
Diepte	mm	205	205	205	230	230
Hoogte	mm	285	285	285	298	298
Gewicht	kg	8,2	8,2	8,2	13,0	13,0
Koudemiddel	Type	R-410A	R-410A	R-410A	R-410A	R-410A
Inspuiting	Type/BI-BU	EEV/BU	EEV/BU	EEV/BU	EEV/BU	EEV/BU
Max.leidinglengte	m	20/25	20/25	20/25	20/25	20/25
Max.hoogteverschil	BI/BU m	15	15	15	15	15
Max.hoogteverschil	BI/BI m	7,5	7,5	7,5	7,5	7,5
Vloeistof leiding	inch	1/4"	1/4"	1/4"	1/4"	1/4"
Zuiggas leiding	inch	3/8"	3/8"	3/8"	1/2"	5/8"